

Assemble Instruction:

We strongly recommend having this fixture installed by a licensed electrician. Before beginning, ensure the power is turned off at the main fuse or circuit breaker box. Please note that actual parts may vary slightly by model.

**** Please note that actual parts may vary slightly by model.**

Steps for installation:

1. Carefully take all parts out of the box before throwing the carton away.
2. Secure the crossbar to the outlet box, ensuring the ground screw faces downward.
3. Screw the nipple into the crossbar.
4. Adjust the nipple so it extends $\frac{1}{4}$ " beyond the canopy.
5. Remove any extra links from the hanging chain, leaving 6" of lead wire beyond the chain.
6. Attach the top loop to the canopy using the nipple.
7. Feed the lead and ground wires through the side chain holder, top glass, check ring, and bottom loop, securing them with the nipple.
8. Attach the assembled top glass to the hanging chain.
9. Run the lead and ground wires through the chain, top loop, and nipple, and into the outlet box.
10. If needed, secure the ground wire to the green screw.
11. Connect the ridged lead wire to the white wire using a wire nut, and connect the smooth lead wire to the black wire in the box with another wire nut.
12. Place the band around the neck of the bell glass.
13. After installing the bulbs, attach the bell glass to the hooks on the band using the three side chains.
14. Finally, turn the circuit breaker back on.

